

Product data sheet


AXEL
9.116.2152.01
LEIPZIGER LEUCHTEN



IP
65


Mounting height of 4.00 m provides optimal light distribution. - Housing and frame made of corrosion-resistant and robust cast aluminium, painted - Attachment made of impact-resistant, UV-stabilized polycarbonate with beaded texture, fitted into frame - Lamp and high-quality mirror optics protected by hinged frame witch can be opened with a tool - Reflector parts made of highest grade aluminium, burnished and anodized - All electrical components are arranged on a block, control gear can be switched over - Available in any RAL or DB colour without surcharge - Pole bracket and luminaire mount hot galvanized and painted - Scope of supply includes cylindrically offset pole, dia. 76 mm, reinforced wall, extended earthing strip made of hot galvanized steel, painted Voltage: 230V 50Hz Protected to: IP 65 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	50 W	LOR	56%
Lamp flux	4200 lm	Total flux	2367 lm
Luminous efficacy	36 lm/W	Total power	66 W
CCT	2000 K		
CRI	25		



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	56%
Lamp flux	6600 lm	Total flux	3720 lm
Luminous efficacy	45 lm/W	Total power	83 W
CCT	2000 K		
CRI	25		

Mounting mode

Pole top mounted

Electric

System power: 66-83 W

Shape and measurements

Length: 14.96 in

Width: 7.87 in

Height: 7.87 in

Protection

IP: 65