Product data sheet


LUCAS X (1-ARMED BEADED) 9.850.3162.16 LEIPZIGER LEUCHTEN






Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

| Nominal lamp power | 125 W | LOR | 83% |
|--------------------|---------|-------------|---------|
| Lamp flux | 6800 lm | ULOR | 2% |
| Luminous efficacy | 41 lm/W | Total flux | 5637 lm |
| CCT | 3400 K | Total power | 137 W |
| CRI | 54 | | |
| | | | |



1 x High pressure mercury vapour lamp

| Nominal lamp power | 80 W | LOR | 83% |
|--------------------|---------|-------------|---------|
| Lamp flux | 4000 lm | ULOR | 2% |
| Luminous efficacy | 37 lm/W | Total flux | 3316 lm |
| CCT | 3400 K | Total power | 89 W |
| CRI | 54 | | |
| | | | |

| Mounting mode | Electric |
|------------------------|------------------------|
| Pole top mounted | System power: 89-137 W |
| Shape and measurements | Protection |
| Height: 19.69 in | IP: 55 |
| Diameter: 22.44 in | |