Product data sheet

VOLKMAR I (WALL FITTING) 9.840.0013.08

LEIPZIGER LEUCHTEN









For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant opal polyethylene attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury	y vapour lamp		
Nominal lamp power	50 W	LOR	73%
Lamp flux	2000 lm	ULOR	28%
Luminous efficacy	25 lm/W	Total flux	1454 lm
CCT	3400 K	Total power	59 W
CRI	54		



1 x High pressure mercury	/ vapour lamp		
Nominal lamp power	80 W	LOR	73%
Lamp flux	4000 lm	ULOR	28%
Luminous efficacy	33 lm/W	Total flux	2908 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Wall mounted

Shape and measurements

Height: 16.14 in Diameter: 16.14 in Electric

System power: 59-89 W

Protection

IP: 55