# Product data sheet

NADJA I (1-ARMED) 9.870.1072.05

LEIPZIGER LEUCHTEN








Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x Metal halide lamp	
Nominal lamp power	150 W
Lamp flux	15000 lm
Luminous efficacy	68 lm/W
CCT	2900 K
CRI	90

LOR	77%
Total flux	11575 lm
Total power	170 W

### Mounting mode

Pole top mounted

# Shape and measurements

Height: 20.08 in Diameter: 20.08 in

## Electric

System power: 170 W

#### Protection

IP: 55

Designation labels: CE