


Product data sheet

RICHARD IV (1-ARMED)
9.892.5547.15
LEIPZIGER LEUCHTEN



Mounting height approx. 3.00 - 4.50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Circular shield for glare limitation made of anodized aluminium - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 60 mm, separately Order pole for double-bracket luminaire, dia. 76 mm, separately

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	42 W	LOR	55%
Lamp flux	3200 lm	ULOR	13%
Luminous efficacy	38 lm/W	Total flux	1769 lm
CCT	2899 K	Total power	46 W
CRI	90		

Mounting mode

Pole top mounted, Ceiling mounted

Shape and measurements

Height: 19.88 in
Diameter: 7.87 in

Design

Material impression: Matt
Color of housing: White

Electric

System power: 46 W
Ballast: ECG
Controller: DALI
Suitable for feed-through wiring

Protection

Designation labels: CE

Other operating numbers

Ambient temperature range: -13...95°F