


Product data sheet

PURE 1
09.1610/HI-PAR/35W/24°38°60°
FLOS




Recessed luminaire for indoor application. For very low voltage halogen lamps or standard and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double Teflon insulation.


Light output 1



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	3269 lm	LOR	70%
Luminous efficacy	65 lm/W	Total flux	2273 lm
CCT	3000 K	Total power	35 W
CRI	84		



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	3269 lm	LOR	63%
Luminous efficacy	59 lm/W	Total flux	2075 lm
CCT	3000 K	Total power	35 W
CRI	84		



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	3269 lm	LOR	59%
Luminous efficacy	55 lm/W	Total flux	1942 lm
CCT	3000 K	Total power	35 W
CRI	84		

Mounting mode

Ceiling recessed

Electric

System power: 35 W
Appliance Class: II

Shape and measurements

Length: 3.94 in

Width: 3.94 in

Height: 5.51 in

Adjustability

Rotatable, Tilttable

Protection

IP: 20