


Product data sheet

ARA LED
10322023
FLOS



Recessed luminaire for outdoor installation on ceiling or false-ceiling. Configuration: die-cast aluminium structure. EN AB-47100 (low copper content). Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Tempered transparent or sandblasted glass glued to the frame, moulded silicone gaskets.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	5.5 W	CRI	80
Total flux	309 lm	LOR	100%
Luminous efficacy	56 lm/W	Total power	5.5 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.92 in
Width: 4.92 in
Height: 3.74 in

Adjustability

Fixed

Electric

System power: 5.5 W
Appliance Class: III

Protection

IP: 65
IK: 06