


Product data sheet

SL720LED SLXL 87 S/D 8TW WH9016 DALI MP
8720761105910
PERFORMANCE IN LIGHTING



LED free-standing luminaire for interior, including: Steel sheet head, extruded aluminium profile post, steel sheet base, powder painted / Angle of the lamp head adjustable using a set screw / Microprismatic diffuser for efficient light diffusion, glare reduction and a high uniformity / Direct / indirect light distribution / Suitable for simultaneous lighting of 2 workstations / Colour rendering index Ra > 80 / Colour tolerance according to MacAdam = 3 SDCM / Direct share of light dimmable, colour temperature 4000K / Complete with flexible power cord with plug / DALI dimmable / VDU application suitable acc. to EN 12464-1 / Light colour and brightness of indirect light share manually adjustable via Tunable White control / 3000 K colour temperature version on demand / Special colour versions available upon request

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	96 W	CRI	80
Total flux	14474 lm	LOR	100%
Luminous efficacy	151 lm/W	ULOR	89%
		Total power	96 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 39.57 in
Width: 16.93 in
Height: 81.77 in

Design

Color of housing: White

Electric

System power: 96 W
Appliance Class: I

Protection

IP: 20