
Product data sheet

LUCAS IX (1-ARMED) 9.859.2036.15 LEIPZIGER LEUCHTEN




Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1	x High	pressure	sodium	vapour	lamp
---	--------	----------	--------	--------	------

50 W	LOR	80%
3500 lm	ULOR	4%
45 lm/W	Total flux	2788 lm
2000 K	Total power	62 W
25		
	3500 lm 45 lm/W 2000 K	3500 lmULOR45 lm/WTotal flux2000 KTotal power



Nominal lamp power	70 W	LOR	80%
Lamp flux	5600 lm	ULOR	4%
Luminous efficacy	54 lm/W	Total flux	4461 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode Electric	
Pole top mounted System	power: 62-83 W
Shape and measurements Protecti	ion
Height: 23.62 in IP: 55	
Diameter: 22.44 in Designa	ation labels: CE, F