



Product data sheet

EASY KAP 105
03.4455.74/QR-CBC/50W/10°24°36°60°
FLOS




Luminaire for recessed mounting on ceilings for halogen, metal halide and LED lamps. The Easy Kap version, incorporates body injected in zamak with liquid paint finish and outer diameter of 105mm with opal glass diffuser. Pre-frame instalation not necessary. The Kap version incorporates body injected in aluminium with liquid paint finish. It is available in two sizes: 105mm and 145mm, always in No Trim installation. Main view made of anodized gloss aluminium with diffuser element made in borosilicate glass. Lampholders with heatsink element in injected aluminium and embedment ring of the optical body in thermoplastic material. Finishings: white (B1), matt gold (GL), blue (BU) and black (74).

Light output 1




1 x Halogen low voltage lamp without reflector

| | | | |
|--------------------|--------|-------------|--------|
| Nominal lamp power | 50 W | Socket | Gx5.3 |
| Lamp flux | 857 lm | LOR | 54% |
| Luminous efficacy | 9 lm/W | Total flux | 463 lm |
| CCT | 3000 K | Total power | 50 W |
| CRI | 99 | | |




1 x Halogen low voltage lamp without reflector

| | | | |
|--------------------|--------|-------------|--------|
| Nominal lamp power | 50 W | Socket | Gx5.3 |
| Lamp flux | 856 lm | LOR | 54% |
| Luminous efficacy | 9 lm/W | Total flux | 463 lm |
| CCT | 3000 K | Total power | 50 W |
| CRI | 99 | | |



1 x Halogen low voltage lamp without reflector

| | | | |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 50 W | Socket | Gx5.3 |
| Lamp flux | 1182 lm | LOR | 58% |
| Luminous efficacy | 14 lm/W | Total flux | 681 lm |
| CCT | 3000 K | Total power | 50 W |
| CRI | 99 | | |



1 x Halogen low voltage lamp without reflector

| | | | |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 50 W | Socket | Gx5.3 |
| Lamp flux | 1054 lm | LOR | 56% |
| Luminous efficacy | 12 lm/W | Total flux | 589 lm |
| CCT | 3000 K | Total power | 50 W |
| CRI | 99 | | |

Mounting mode

Ceiling recessed

Shape and measurements

Height: 6.38 in
Diameter: 4.13 in

Adjustability

Fixed

Electric

System power: 50 W

Protection

IP: 20