## Product data sheet

DIETER II 9.894.2036.05

LEIPZIGER LEUCHTEN









Recommended mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Special steel frame, painted - Large aluminium reflector, underside finished in special white paint for max. light reflection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - All electrical components on one block - Adapter jack connection - Lamps are easy to change -Available in any RAL or DB color without surcharge - Please order pole mount dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 65 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



1 x High pressure sodium vapour lamp		
Nominal lamp power	50 W	
Lamp flux	3500 lm	
Luminous efficacy	29 lm/W	
CCT	2000 k	
CRI	25	

LOR	52%
ULOR	13%
Total flux	1811 lm
Total power	62 W



1 x High pressure sodium vapour	lamp
Nominal lamp power	70 V

Nominal lamp power	70 W	
Lamp flux	5600 lm	
Luminous efficacy	35 lm/W	
CCT	2000 K	
CRI	25	

LOR 52%
ULOR 13%
Total flux 2898 lm
Total power 83 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in Diameter: 10.63 in Electric

System power: 62-83 W

Protection

IP: 65