


Product data sheet

DOWNTOWN NO TRIM EMERGENCY Ø160
03.0275/TC-TEL/18W
FLOS



Luminaires for embedded installation indoor with fluorescent lamps Optical body made in injected aluminium with powder-coated paint finish. Heatsink made in injected aluminium under pressure attached to the body of the luminaire. Lower and upper reflectors available made of anodized aluminium with specular finish. Fixed upper reflector. Inferior reflector formed by self reflector and a spreading lens of 4mm thick and a polycarbonate ring that fixes the reflector to the aluminium ring of the product. Available in two diameters 160mm and 215mm.Luminary with emergency kit for permanent lighting systems using compact fluorescent lamps. Includes combo ballast (inverter+ballast) with Ni-Cd 3hbattery supplied fully connected.

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	18 W	Socket	Gx24Q-2
Lamp flux	1200 lm	LOR	40%
Luminous efficacy	26 lm/W	Total flux	475 lm
CCT	3000 K	Total power	18 W
CRI	84		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 6.30 in
Diameter: 5.83 in

Adjustability

Fixed

Electric

System power: 18 W

Protection

IP: 23