

Product data sheet


KORA VI (1-ARMED)
9.106.4447.05
LEIPZIGER LEUCHTEN



IP
55

One or double-bracket pole luminaire with intensive brightness (height 4.50 and 6.00 m) in order to illuminate streets and footpaths. - Attachment made of plexiglass XT, sandblasted on one side - Computer-optimized reflector systems for high-pressure lamps with clear glass tubular bulbs/DULUX lamps ensures excellent illumination - Special steel luminaire body and unit carrier, available painted in any RAL or DB colour without surcharge, or ground and passivated - Luminaire case fold out for lamp change - Adapter jack connection - Included pole door to take in a cable joint box - Scope of supply includes square pole, incl. special steel bracket and electrical supply element (intermediate unit, ignition unit, condenser) - Available for 3 fastening variants in the ground: flange sheet, flange sheet in order to pave over, or end piece, situated at the pole, to set in the ground Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



2 x Compact fluorescent lamp

Nominal lamp power	40 W	LOR	44%
Lamp flux	3500 lm	ULOR	2%
Luminous efficacy	34 lm/W	Total flux	3097 lm
CCT	2899 K	Total power	90 W
CRI	90		

Mounting mode

Pole integrated

Electric

System power: 90 W

Shape and measurements

Length: 41.73 in

Width: 11.81 in

Height: 3.94 in

Protection

IP: 55