Product data sheet

PAULA V 9.645.3162.05

LEIPZIGER LEUCHTEN









Recommended mounting height 4.50 - 6.00 m, other heigts please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order special pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



| 1 x High pressure mercury | vapour lamp |
|---------------------------|-------------|
| Nominal lamp power | 125 W |
| Lamp flux | 6800 lm |
| Luminous efficacy | 41 lm/W |
| CCT | 3400 k |
| CRI | 54 |

| LOR | 83% |
|-------------|---------|
| Total flux | 5651 lm |
| Total power | 137 W |
| | |



| 1 x High pressure mercury vapour lamp | | | | |
|---------------------------------------|---------|-------------|---------|--|
| Nominal lamp power | 80 W | LOR | 83% | |
| Lamp flux | 4000 lm | Total flux | 3324 lm | |
| Luminous efficacy | 37 lm/W | Total power | 89 W | |
| CCT | 3400 K | | | |
| CRI | 54 | | | |

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.74 in Diameter: 28.74 in Electric

System power: 89-137 W

Protection

IP: 55