Product data sheet

MARCEL II 9.791.2056.00











For medium and high light requirements, mounting height 3.80 m. - Impact-resistant clear polycarbonate attachment, UV-stabilized, - Reflector lamellae made of premium highest-grade aluminium, burnished and anodized for light guidance and glare limitation - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection -Available in any RAL or DB colour without surcharge - Scope of supply includes fork bracket,post dia. 76 mm (for 3.80 m mounting height) and ornamental ring, painted Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp		
Nominal lamp power	100 W	
Lamp flux	10400 lm	
Luminous efficacy	54 lm/W	
CCT	2000 k	
CRI	25	

LOR	60%
ULOR	10%
Total flux	6215 lm
Total power	115 W



i x migri pressure socium vapour iamp		
Nominal lamp power	70 W	
Lamp flux	5600 lm	
Luminous efficacy	40 lm/W	
CCT	2000 K	
CRI	25	

1 v High proceure codium vanour lamp

LOR	60%
ULOR	10%
Total flux	3346 lm
Total power	83 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 33.27 in Diameter: 20.08 in Electric

System power: 83-115 W

Protection

IP: 55