

Product data sheet

NADJA VII (1-ARMED BEADED)

9.876.3066.86

LEIPZIGER LEUCHTEN




Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	125 W	LOR	78%
Lamp flux	6800 lm	Total flux	5302 lm
Luminous efficacy	39 lm/W	Total power	137 W
CCT	3400 K		
CRI	54		



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	78%
Lamp flux	4000 lm	Total flux	3119 lm
Luminous efficacy	35 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

Mounting mode

Pole top mounted, Ceiling mounted

Shape and measurements

Height: 16.54 in

Diameter: 16.54 in

Design

Material impression: Matt

Color of housing: White

Glare protection

Glare protection: UGR < 19

Electric

System power: 89-137 W

Ballast: ECG

Controller: DALI

Protection

IP: 55

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 32...95°F