


Product data sheet

PURE 3 SPOT TRACK
09.1918/QR-111/75W/8°24°45°
FLOS




Luminaire for three-phase electric track installation. For very low voltage halogen lamps or standar and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double teflon insulation.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	75 W	Socket	G53
Lamp flux	707 lm	LOR	100%
Luminous efficacy	9 lm/W	Total flux	707 lm
CCT	3000 K	Total power	75 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	75 W	Socket	G53
Lamp flux	871 lm	LOR	100%
Luminous efficacy	12 lm/W	Total flux	872 lm
CCT	3000 K	Total power	75 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	G5.3
Lamp flux	413 lm	LOR	101%
Luminous efficacy	6 lm/W	Total flux	415 lm
CCT	4000 K	Total power	75 W
CRI	99		

Mounting mode

Ceiling mounted

Electric

System power: 75 W
Appliance Class: I

Shape and measurements

Length: 1.69 in

Width: 5.63 in

Height: 6.22 in

Adjustability

Free

Protection

IP: 20