Product data sheet

LUCAS II (WALL FITTING) 9.836.3162.15

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| 1 x High pressure mercury | vapour lamp |
|---------------------------|-------------|
| Nominal lamp power | 125 W |
| Lamp flux | 6800 lm |
| Luminous efficacy | 42 lm/W |
| CCT | 3400 k |
| CRI | 54 |

LOR 84%
Total flux 5697 lm
Total power 137 W



| 1 x High pressure mercury vapour lamp | | | |
|---------------------------------------|---------|-------------|--|
| Nominal lamp power | 80 W | LOR | |
| Lamp flux | 4000 lm | Total flux | |
| Luminous efficacy | 38 lm/W | Total power | |
| CCT | 3400 K | | |
| CDI | 5.4 | | |

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in Electric

System power: 89-137 W

Protection

IP: 55

84% 3351 lm 89 W