


Product data sheet

SKOT WALL LED 3000K 6.5W HALF SHADED CLEAR
91520-1002
LOUIS POULSEN



Skot Wall/Ceiling Design: LK as Light concept : The fixture is available with two types of distribution: symmetric or asymmetric. The asymmetric is only recommended for wall mounting. The opal diffuser creates a soft light distribution. Finish: Aluminium coloured or graphite with textured surface, powder coated. Material: Diffuser: injection moulded clear polycarbonate or injection moulded opal polycarbonate. Base/cross guard: Die cast aluminium. Mounting: Terminal block: 1x4x2,5mm². Cable entries: 2x rear entries. 1x top entry, 1x side entry in each side and 3x bottom entries. Looping: Approved, max. 4x1,5mm² Weight: Max. 2,5 kg Class: Ingress protection IP66. Electric shock protection II w/o ground. IK10.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	80
Total flux	505 lm	LOR	100%
Luminous efficacy	78 lm/W	ULOR	6%
		Total power	6.5 W

Mounting mode

Wall mounted

Shape and measurements

Height: 4.53 in
Diameter: 9.41 in

Adjustability

Fixed

Electric

System power: 6.5 W
Appliance Class: II

Protection

IP: 66