

# Product data sheet


MORITZ II (1-ARMED)  
9.117.3162.02  
LEIPZIGER LEUCHTEN



IP  
55


Mounting height of 4.50 to 6.00 m for medium or high light requirements - Luminaire made of cast aluminium, varnished - Superior lighting due to computer-optimised reflector system for sodium vapour high pressure discharge with clear glass tube bulb - Cover of single-pane safety glass, hinged - Cable protection hosing made of braided stainless steel - All electrical parts fitted -Available in any required RAL or DB colour without extra price - Special  $\varnothing$ 102 mm pole for 4.50 m mounting height,  $\varnothing$ 114 mm pole for 6.00 m mounting height, including pole mounting hot-dip galvanised and varnished are part of the delivery Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	125 W	LOR	82%
Lamp flux	6800 lm	Total flux	5579 lm
Luminous efficacy	41 lm/W	Total power	137 W
CCT	3400 K		
CRI	54		



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	82%
Lamp flux	4000 lm	Total flux	3282 lm
Luminous efficacy	37 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 21.26 in  
Width: 21.26 in  
Height: 6.89 in

## Electric

System power: 89-137 W

## Protection

IP: 55