

Product data sheet

LUCAS IX (1-ARMED BEADED)
9.859.5507.16
LEIPZIGER LEUCHTEN



IP
55

Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



2 x Compact fluorescent lamp

Nominal lamp power	26 W	LOR	80%
Lamp flux	1800 lm	ULOR	4%
Luminous efficacy	51 lm/W	Total flux	2879 lm
CCT	2899 K	Total power	56 W
CRI	90		

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.62 in

Diameter: 22.44 in

Electric

System power: 56 W

Protection

IP: 55