
Product data sheet

NADJA V (2-ARMED) 9.871.3062.85

LEIPZIGER LEUCHTEN








Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



| 1 x High pressure mercury | vapour lamp |
|---------------------------|-------------|
| Nominal lamp power | 125 W |
| Lamp flux | 6800 lm |
| Luminous efficacy | 38 lm/W |
| CCT | 3400 K |
| CRI | 54 |

LOR 77% Total flux 5247 lm Total power 137 W

Light output 2



| 1 x High pressure mercury vapour lamp | | | |
|---------------------------------------|---------|-------------|---------|
| Nominal lamp power | 125 W | LOR | 77% |
| Lamp flux | 6800 lm | Total flux | 5247 lm |
| Luminous efficacy | 38 lm/W | Total power | 137 W |
| CCT | 3400 K | | |

54

Electric

Mounting mode

System power: 274 W Pole top mounted

CRI

Shape and measurements

Protection Height: 20.08 in IP: 55

Diameter: 20.08 in