


# Product data sheet

GEORG V (1-ARMED)  
9.870.0125.04  
LEIPZIGER LEUCHTEN




With mounting heights between 3.00 and 4.00 m for medium and low light requirements. - Large shade, inside in special white paint for better reflection - Luminaire body made of aluminium/galvanized steel sheet, outside painted in colour, inside finished in special white pain - Impact-resistant polyethylene attachment rotates and locks into place for easy lamp replacement - Steel tubing galvanized and painted -Wired ready for connection - Connetion by adapter jack -Available in any RAL or DB colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm,and pole for multi-bracket luminaire, dia. 76 mm,separately Voltage: 230V 50Hz Protected to: IP 54 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



### 1 x High pressure sodium vapour lamp

Nominal lamp power	50 W	LOR	72%
Lamp flux	3500 lm	ULOR	4%
Luminous efficacy	41 lm/W	Total flux	2515 lm
CCT	2000 K	Total power	62 W
CRI	25		



### 1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	72%
Lamp flux	5600 lm	ULOR	4%
Luminous efficacy	48 lm/W	Total flux	4025 lm
CCT	2000 K	Total power	83 W
CRI	25		

## Mounting mode

Pole top mounted, Ceiling mounted

## Shape and measurements

Height: 28.35 in  
Diameter: 22.83 in

## Design

Material impression: Matt  
Color of housing: White

## Electric

System power: 62-83 W  
Ballast: ECG  
Controller: DALI  
Suitable for feed-through wiring

## Protection

IP: 54  
Designation labels: CE

#### Other operating numbers

Ambient temperature range: -4...95°F