

# Product data sheet


ASL 2010/1  
9.135.7032.41  
LEIPZIGER LEUCHTEN



IP  
65

recom. pole height: 4.50m – 10.00m light standards: low, medium and high lighting requirements lamp: excl. metal halide, sodium or compact fluorescent lamp; incl. CosmoPolis gear: HCI and NAV: incl. low loss ballast, ignitor and condensator; electronic ballast on request; CDO, CPO, compact fluorescent lamp: incl. electronic ballast light control: at extra cost: power reduction, dimming, night switch optical system: reflector system for clear, tubular high pressure or for compact fluorescent lamps light distribution: asymmetrical wide beam; RWL: extreme narrow wide beam luminaire head: made of cast and die cast aluminium, powder coated colour: DB 703; other colours on request glazing: polycarbonate, clear, impact resistant, UVstabilised, to be hinged down wiring: via a plug and socket connector within the luminaire head installation: for top entry  $\varnothing$  76mm and  $\varnothing$  60mm, inclination 5° resp. 10° or for side entry  $\varnothing$  60mm; dispatch standard: for top entry, 5° accessory: lamp (except for CPO), cable, column, pole accessories, wall, corner or column bracket - to be ordered separately application areas: parkways, cycle lanes, residential and local distribution roads, main streets, boulevards, pedestrian zones, car parks, schools, home for elderly people, hotels, factory premises, squares, pedestrian crossings

## Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	LOR	89%
Lamp flux	7200 lm	ULOR	3%
Luminous efficacy	78 lm/W	Total flux	6375 lm
CCT	3000 K	Total power	82 W
CRI	90		

## Mounting mode

Pole top mounted

## Electric

System power: 82 W

## Shape and measurements

Length: 27.95 in  
Width: 11.81 in  
Height: 7.32 in  
Weight: 7.5 kg

## Protection

IP: 65

## Adjustability

Height adjustable