


# Product data sheet

NADJA I (WALL FITTING BEADED)  
9.840.3142.06  
LEIPZIGER LEUCHTEN




Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	50 W	LOR	78%
Lamp flux	2000 lm	Total flux	1559 lm
Luminous efficacy	26 lm/W	Total power	59 W
CCT	3400 K		
CRI	54		



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	78%
Lamp flux	4000 lm	Total flux	3119 lm
Luminous efficacy	35 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

## Mounting mode

Wall mounted

## Shape and measurements

Height: 20.08 in

Diameter: 20.08 in

## Design

Material impression: Matt

Color of housing: Black

## Electric

System power: 59-89 W

Ballast: ECG

## Protection

IP: 55

Designation labels: CE

## Other operating numbers

Ambient temperature range: -4...77°F