

# Product data sheet

VOLKMAR I (WALL FITTING)


9.840.0080.08

LEIPZIGER LEUCHTEN




For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant opal polyethylene attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	125 W	LOR	73%
Lamp flux	6800 lm	ULOR	28%
Luminous efficacy	36 lm/W	Total flux	4944 lm
CCT	3400 K	Total power	137 W
CRI	54		



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	73%
Lamp flux	4000 lm	ULOR	28%
Luminous efficacy	33 lm/W	Total flux	2908 lm
CCT	3400 K	Total power	89 W
CRI	54		

## Mounting mode

Wall mounted, Ceiling mounted

## Shape and measurements

Height: 16.14 in

Diameter: 16.14 in

## Design

Material impression: Matt

## Electric

System power: 89-137 W

Ballast: ECG

## Protection

IP: 55

Designation labels: CE, ENEC

## Other operating numbers

Ambient temperature range: 32...95°F