

Product data sheet

PAULA I
9.641.3046.05
LEIPZIGER LEUCHTEN



IP
55

Recommended mounting height 4.50 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - all designs to suit non-glare class KB 1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack - Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp

| | |
|--------------------|---------|
| Nominal lamp power | 50 W |
| Lamp flux | 2000 lm |
| Luminous efficacy | 28 lm/W |
| CCT | 3400 K |
| CRI | 54 |

| | |
|-------------|---------|
| LOR | 83% |
| Total flux | 1662 lm |
| Total power | 59 W |



1 x High pressure mercury vapour lamp

| | |
|--------------------|---------|
| Nominal lamp power | 80 W |
| Lamp flux | 4000 lm |
| Luminous efficacy | 37 lm/W |
| CCT | 3400 K |
| CRI | 54 |

| | |
|-------------|---------|
| LOR | 83% |
| Total flux | 3324 lm |
| Total power | 89 W |

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.74 in

Diameter: 28.74 in

Electric

System power: 59-89 W

Protection

IP: 55