

# Product data sheet


PAULA III (BEADED)  
9.643.1052.06  
LEIPZIGER LEUCHTEN



IP  
55

Recommended mounting height 4.50 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - all designs to suit non-glare class KB 1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack - Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x Metal halide lamp

Nominal lamp power	100 W	LOR	86%
Lamp flux	10000 lm	Total flux	8622 lm
Luminous efficacy	75 lm/W	Total power	115 W
CCT	3000 K		
CRI	90		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 28.74 in  
Diameter: 28.74 in

## Electric

System power: 115 W

## Protection

IP: 55