


# Product data sheet

JACKIE LED  
8412700  
FLOS



• Outdoor luminaire for installation on wall. • Die-cast aluminium structure. EN AB-47100 alloy (low copper content). • Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Tempered transparent glass, expanded-silicone gaskets.

## Light output 1



1 x LED			
Nominal lamp power	4 W	LOR	99%
Lamp flux	273 lm	Total flux	269 lm
Luminous efficacy	54 lm/W	Total power	5 W
CCT	6000 K		
CRI	70		

## Mounting mode

Wall mounted

## Shape and measurements

Height: 2.76 in  
Diameter: 2.76 in

## Adjustability

Fixed

## Electric

System power: 5 W  
Appliance Class: I

## Protection

IP: 54  
IK: 08