
## Product data sheet

LUCAS VIII (1-ARMED BEADED) 9.858.2032.16

LEIPZIGER LEUCHTEN








High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately, inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



| 1 x High pressure sodium vapour lam |
|-------------------------------------|
|-------------------------------------|

| Nominal lamp power | 70 W    | LOR         | 80%     |
|--------------------|---------|-------------|---------|
| Lamp flux          | 5600 lm | ULOR        | 4%      |
| Luminous efficacy  | 54 lm/W | Total flux  | 4479 lm |
| CCT                | 2000 K  | Total power | 83 W    |
| CBI                | 25      |             |         |

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.62 in Diameter: 22.44 in Electric

System power: 83 W

Protection

IP: 55