

Product data sheet


泛光灯
PAK460103 PAK-L83-150A-AF-L
PAK



IP
65


专利圆弧型一体化设计，高压铸铝成型灯体，反射罩采用高纯阳极电镀铝，高强度钢化玻璃，安全活页装置，四角下压式锁扣设计，适配光源：150W/Rx7S非对称型 金卤/高压钠 IP等级：IP65 适用于建筑泛光照明、广告招牌照明、体育馆、货场、码头和庭院道路等照明。

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	150 W	Socket	Rx7S
Lamp flux	15000 lm	LOR	73%
Luminous efficacy	68 lm/W	Total flux	10989 lm
CCT	2000 K	Total power	162.4 W
CRI	31		



1 x Metal halide lamp

Nominal lamp power	150 W	Socket	Rx7S
Lamp flux	13500 lm	LOR	73%
Luminous efficacy	61 lm/W	Total flux	9890 lm
CCT	4000 K	Total power	162.4 W
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 7.28 in
Width: 12.63 in
Height: 3.89 in

Adjustability

Tiltable

Electric

System power: 162.4 W

Protection

IP: 65