Product data sheet

LOUIS I (WALL FITTING) 9.745.2152.07


LEIPZIGER LEUCHTEN






Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lamp				
Nominal lamp power	50 W	LOR		
Lamp flux	3500 lm	ULOR		
Luminous efficacy	32 lm/W	Total flux		
CCT	2000 K	Total power		
CRI	25			



i x High pressure sodium vapour lamp				
Nominal lamp power	70 W	LOR	56%	
Lamp flux	5600 lm	ULOR	14%	
Luminous efficacy	38 lm/W	Total flux	3131 lm	
CCT	2000 K	Total power	83 W	
CRI	25			

Mounting mode

Wall mounted

Shape and measurements

Height: 7.87 in Diameter: 7.87 in Electric

System power: 62-83 W

Protection

IP: 55

56% 14% 1957 lm 62 W