

Product data sheet

RICHARD II (2-ARMED)
9.893.1032.00
LEIPZIGER LEUCHTEN



IP
55


Mounting height approx. 3,00 - 4,50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Circular shield for glare limitation made of anodized aluminium - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge -Order pole, dia. 60 mm, separately Order pole for double-bracket luminaire, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	LOR	43%
Lamp flux	7200 lm	ULOR	8%
Luminous efficacy	35 lm/W	Total flux	3094 lm
CCT	3000 K	Total power	89 W
CRI	90		

Light output 2



1 x Metal halide lamp			
Nominal lamp power	70 W	LOR	43%
Lamp flux	7200 lm	ULOR	8%
Luminous efficacy	35 lm/W	Total flux	3094 lm
CCT	3000 K	Total power	89 W
CRI	90		

Mounting mode	Electric
Pole top mounted	System power: 178 W
Shape and measurements	Protection
Height: 24.21 in	IP: 55
Diameter: 9.84 in	