


Product data sheet

MEMI
491600
FLOS



• Outdoor luminaire for installation on wall or on dedicated post. • Configuration: die-cast aluminium structure. EN AB-47100 alloy (low copper content). • Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Tempered sandblasted glass, silicone gaskets.

Light output 1



2 x Compact fluorescent lamp			
Nominal lamp power	26 W	Socket	G24D-2
Lamp flux	1800 lm	LOR	18%
Luminous efficacy	12 lm/W	Total flux	635 lm
CCT	3850 K	Total power	52 W
CRI	79		

Mounting mode

Wall mounted, Standing / Bollard

Shape and measurements

Length: 11.81 in
Width: 5.91 in
Height: 7.87 in

Adjustability

Fixed

Electric

System power: 52 W
Appliance Class: I

Protection

IP: 65
IK: 07