

# Product data sheet

NADJA II (2-ARMED BEADED)  
9.874.3142.06  
LEIPZIGER LEUCHTEN



IP  
55

Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



### 1 x High pressure mercury vapour lamp

|                    |         |
|--------------------|---------|
| Nominal lamp power | 50 W    |
| Lamp flux          | 2000 lm |
| Luminous efficacy  | 26 lm/W |
| CCT                | 3400 K  |
| CRI                | 54      |

|             |         |
|-------------|---------|
| LOR         | 78%     |
| Total flux  | 1559 lm |
| Total power | 59 W    |



### 1 x High pressure mercury vapour lamp

|                    |         |
|--------------------|---------|
| Nominal lamp power | 80 W    |
| Lamp flux          | 4000 lm |
| Luminous efficacy  | 35 lm/W |
| CCT                | 3400 K  |
| CRI                | 54      |

|             |         |
|-------------|---------|
| LOR         | 78%     |
| Total flux  | 3119 lm |
| Total power | 89 W    |

## Light output 2



### 1 x High pressure mercury vapour lamp

|                    |         |
|--------------------|---------|
| Nominal lamp power | 50 W    |
| Lamp flux          | 2000 lm |
| Luminous efficacy  | 26 lm/W |
| CCT                | 3400 K  |
| CRI                | 54      |

|             |         |
|-------------|---------|
| LOR         | 78%     |
| Total flux  | 1559 lm |
| Total power | 59 W    |



1 x High pressure mercury vapour lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 80 W    | LOR         | 78%     |
| Lamp flux          | 4000 lm | Total flux  | 3119 lm |
| Luminous efficacy  | 35 lm/W | Total power | 89 W    |
| CCT                | 3400 K  |             |         |
| CRI                | 54      |             |         |

Mounting mode

Pole top mounted

Shape and measurements

Height: 20.08 in  
Diameter: 20.08 in

Electric

System power: 118-178 W

Protection

IP: 55