

# Product data sheet


RICHARD V  
9.889.3162.00  
LEIPZIGER LEUCHTEN



IP  
55


Mounting height approx. 4.00 m - 5.00 m, for medium light requirements. - Impact-resistant clear polycarbonat cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	125 W	LOR	59%
Lamp flux	6800 lm	ULOR	15%
Luminous efficacy	29 lm/W	Total flux	4023 lm
CCT	3400 K	Total power	137 W
CRI	54		



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	59%
Lamp flux	4000 lm	ULOR	15%
Luminous efficacy	27 lm/W	Total flux	2367 lm
CCT	3400 K	Total power	89 W
CRI	54		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 24.21 in  
Diameter: 9.84 in

## Electric

System power: 89-137 W

## Protection

IP: 55