



# Product data sheet

EMMA150  
11815142  
FLOS



• Outdoor luminaire for installation on wall. • Configuration: die-cast aluminium fixing base and frames, EN AB47100 alloy (low copper content). Extruded aluminium body. • Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Tempered transparent glass, silicone gaskets.

## Light output 1



### 2 x Compact fluorescent lamp

Nominal lamp power	26 W	Socket	Gx24Q-3
Lamp flux	1800 lm	LOR	32%
Luminous efficacy	22 lm/W	ULOR	16%
CCT	3000 K	Total flux	1147 lm
CRI	84	Total power	52 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 5.91 in  
Diameter: 5.91 in

## Adjustability

Fixed

## Electric

System power: 52 W  
Appliance Class: I

## Protection

IP: 65  
IK: 07