# Product data sheet

PH LOUVRE LED 2700K 96W 5741094655


LOUIS POULSEN





PH Louvre Design : Poul Henningsen Light concept : The fixture provides 100% glare-free light. The geometrical, spherical design is based on the principle of illuminating all surfaces at the same angle. This ensures uniform light around the fixture, illuminating both walls and ceiling. Matte painted undersurfaces and glossy top surfaces result in an attractive reflection of the diffused light, creating uniform light distribution around the fixture. Finish: White, wet painted. Material: Shades: Spun aluminium. Frame: High lustre chrome plated, extruded brass. Housing: High lustre chrome plated, spun aluminium. Mounting: Suspension type: Cable 3x0,75mm<sup>2</sup> & wire. Canopy: Yes. Cable length: 4m. Weight: Max. 7kg. Class: Ingress protection IP20. Electric shock protection I w. ground.

## Light output 1 (integrated)



CCT 2700 K Lamp type LED Nominal lamp power 96 W CRI 90 LOR 100% Total flux 2740 lm 29 lm/W Luminous efficacy ULOR 18% Total power 96 W

#### Mounting mode

Pendant

Shape and measurements

Height: 25.59 in Diameter: 23.62 in

#### Adjustability

Fixed

## Electric

System power: 96 W Appliance Class: I

## Protection

IP: 20