


Product data sheet

CIELO LED
94186131
FLOS



Recessed linear luminaire for outdoor/indoor installation in ground or ceiling. • Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Die-cast double closing end on each side allowing easy and safe maintenance, moulded silicone gasket, 8mm thick tempered transparent glass with silkscreen border mechanically fixed to the body by a silicone adhesive.Electrical components are installed on a removable frame.

Light output 1



1 x LED			
Nominal lamp power	14.4 W	LOR	98%
Lamp flux	1028 lm	ULOR	98%
Luminous efficacy	63 lm/W	Total flux	1010 lm
CCT	4000 K	Total power	16 W
CRI	80		

Mounting mode

Floor recessed

Shape and measurements

Length: 25.39 in
Width: 3.94 in
Height: 3.11 in

Adjustability

Fixed

Electric

System power: 16 W
Appliance Class: I

Protection

IP: 67
IK: 09