


# Product data sheet

NADJA V (2-ARMED BEADED)

9.871.3142.86


LEIPZIGER LEUCHTEN



IP  
55

Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	50 W
Lamp flux	2000 lm
Luminous efficacy	26 lm/W
CCT	3400 K
CRI	54

LOR	78%
Total flux	1559 lm
Total power	59 W




### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	35 lm/W
CCT	3400 K
CRI	54

LOR	78%
Total flux	3119 lm
Total power	89 W


## Light output 2



### 1 x High pressure mercury vapour lamp

Nominal lamp power	50 W
Lamp flux	2000 lm
Luminous efficacy	26 lm/W
CCT	3400 K
CRI	54

LOR	78%
Total flux	1559 lm
Total power	59 W



**1 x High pressure mercury vapour lamp**

Nominal lamp power	80 W	LOR	78%
Lamp flux	4000 lm	Total flux	3119 lm
Luminous efficacy	35 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

**Mounting mode**

Pole top mounted

**Shape and measurements**

Height: 20.08 in

Diameter: 20.08 in

**Electric**

System power: 118-178 W

**Protection**

IP: 55