

Product data sheet

MARCEL II (W. SHIELD ON SIDE FACING BUILDING CLEAR ATTACHMENT)


9.791.3042.20

LEIPZIGER LEUCHTEN



For medium and high light requirements, mounting height 3.80 m. - Impact-resistant clear polycarbonate attachment, UV-stabilized, - Reflector lamellae made of premium highest-grade aluminium, burnished and anodized for light guidance and glare limitation - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection -Available in any RAL or DB colour without surcharge - Scope of supply includes fork bracket,post dia. 76 mm (for 3.80 m mounting height) and ornamental ring, painted Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	47%
Lamp flux	4000 lm	ULOR	7%
Luminous efficacy	21 lm/W	Total flux	1867 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Pole top mounted

Shape and measurements

Height: 33.27 in

Diameter: 20.08 in

Electric

System power: 89 W

Protection

IP: 55