


Product data sheet

COMPASS
03.3500/QR-CBC/50W/10°/24/38°/60°
FLOS




Luminaire for halogen and high-pressure discharge lamps. Recessed body in black-painted metal. Die-cast aluminium alloy, powder-coated closing ring. Die-cast aluminium lamp support with heat dissipating element. Black thermoplastic anti-glare ring, 4 mm tempered glass cover. Stainless steel fixing brackets

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1012 lm	LOR	100%
Luminous efficacy	20 lm/W	Total flux	1012 lm
CCT	3000 K	Total power	50 W
CRI	100		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	995 lm	LOR	100%
Luminous efficacy	20 lm/W	Total flux	995 lm
CCT	3000 K	Total power	50 W
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	1182 lm	LOR	101%
Luminous efficacy	24 lm/W	Total flux	1189 lm
CCT	3000 K	Total power	50 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1025 lm	LOR	100%
Luminous efficacy	21 lm/W	Total flux	1026 lm
CCT	3000 K	Total power	50 W
CRI	100		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 4.72 in

Diameter: 4.33 in

Adjustability

Fixed

Electric

System power: 50 W

Appliance Class: III

Protection

IP: 23