

# Product data sheet


ASL 2010/1 FF LED  
9.135.8318.41-3  
LEIPZIGER LEUCHTEN



IP  
65

windage area: 0.105 (on the side) / 0.045 (front) recom. pole height: 4.50m – 10.00m light standards: low, medium and high lighting requirements lamp: incl. 1, 2 or 3 FF II-X LED module(s) colour temperature: 4.000K neutral white or 3.000K warm white gear: electronic driver, up to 100.000 hours; CLO mode LED life expectancy: up to 50.000 hours/ L100 light control: at extra cost: power reduction, dimming, night switch or CLEVER LIGHT optical system: directed light (multi layer) provided by an exchangeable, anti-aging lens technology light distribution: asymmetrical wide beam luminaire head: made of cast and die cast aluminium, powder coated colour: DB 703; other colours on request glazing: polycarbonate, clear, impact resistant, UV-stabilised, to be hinged down wiring: via a plug and socket connector within the luminaire head installation: for top entry  $\varnothing$  76mm and  $\varnothing$  60mm, inclination 5° resp. 10° or for side entry  $\varnothing$  60mm; dispatch standard: for top entry, 5° accessory: cable, column, pole accessories, wall, corner or column bracket - to be ordered separately application areas: parkways, cycle lanes, residential and local distribution roads, main streets, boulevards, pedestrian zones, car parks, schools, home for elderly people, hotels, factory premises, squares

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	47 W	CRI	70
Total flux	5870 lm	LOR	100%
Luminous efficacy	125 lm/W	Total power	47 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 27.95 in  
Width: 11.81 in  
Height: 7.32 in  
Weight: 10.5 kg

## Adjustability

Height adjustable

## Electric

System power: 47 W

## Protection

IP: 65