

Product data sheet

FLAT POLYMERO
672059.002.5.04
RZB




IP
40

IK
03


Series: FLAT POLYMERO Decorative round surface-mounted luminaire. For escape route illumination. Base: metal, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). Self-contained system with automatic self-test and feedback to the RZB monitoring system MULTIDIGIT. Colour: white Diameter: 460mm Height: 120mm Weight: 2.44kg Operating mode: Non-maintained power mode and maintained power mode Duration time: 3h Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 20W Rated luminous flux: 2100lm Luminous flux, emergency: 200lm System power, emergency: 0W Control gear: Regulated power supply Protection class: I Type of protection: IP40

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	80
Total flux	200 lm	LOR	100%
Luminous efficacy	10 lm/W	ULOR	10%
		Total power	20 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	80
Total flux	2100 lm	LOR	100%
Luminous efficacy	105 lm/W	ULOR	10%
		Total power	20 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.72 in

Diameter: 18.11 in

Electric

System power: 40 W

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 40

IK: 03