


Product data sheet

NADJA III (WALL FITTING)
9.846.3066.05
LEIPZIGER LEUCHTEN




Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 125 W | LOR | 78% |
| Lamp flux | 6800 lm | Total flux | 5317 lm |
| Luminous efficacy | 39 lm/W | Total power | 137 W |
| CCT | 3400 K | | |
| CRI | 54 | | |



1 x High pressure mercury vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 80 W | LOR | 78% |
| Lamp flux | 4000 lm | Total flux | 3128 lm |
| Luminous efficacy | 35 lm/W | Total power | 89 W |
| CCT | 3400 K | | |
| CRI | 54 | | |

Mounting mode

Wall mounted

Shape and measurements

Height: 16.54 in

Diameter: 16.54 in

Design

Material impression: Matt

Color of housing: White

Electric

System power: 89-137 W

Ballast: ECG

Protection

IP: 55

Designation labels: CE

Other operating numbers

Ambient temperature range: 32...95°F