

# Product data sheet

EVA II (W. SHIELD ON SIDE FACING BUILDING)


9.898.2056.25

LEIPZIGER LEUCHTEN




For high light requirements, mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate attachment, UV-stabilized - Large aluminium reflector for max. light output, inside in special white paint - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Unit carrier made of hot die cast aluminium, corrosion-resistant, outside painted in colour - All electrical components are arranged on a block - Adapter jack for connection -Available in any RAL or DB colour without surcharge - Please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x High pressure sodium vapour lamp

Nominal lamp power	100 W	LOR	48%
Lamp flux	10400 lm	ULOR	10%
Luminous efficacy	44 lm/W	Total flux	5005 lm
CCT	2000 K	Total power	115 W
CRI	25		



### 1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	48%
Lamp flux	5600 lm	ULOR	10%
Luminous efficacy	32 lm/W	Total flux	2695 lm
CCT	2000 K	Total power	83 W
CRI	25		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 17.72 in

Diameter: 15.75 in

## Electric

System power: 83-115 W

## Protection

IP: 55