

# Product data sheet


ASL 2060  
9.139.7052.02  
LEIPZIGER LEUCHTEN



IP  
65


recom. pole height: 4.50m – 12.00m light standards: low, medium and high lighting requirements lamp: excl. metal halide or sodium lamp; incl. CosmoPolis or incl. LED modules, easy to replace: incl. 1 glare-free LLM LED module 1 ; incl. 1, or 2 FF II-X or FF SW-X LED module(s) 7 colour temperature: 3.000K warm white, 4.000K neutral white gear: HCI and NAV: incl. low loss ballast, ignitor and condensator; electronic ballast on request; CDO, CPO: incl. electronic ballast; LED: electronic driver, depending on the model: up to 50.000 to 100.000 hours; CLO mode LED life expectancy: up to 50.000 hours/ L100 light control: at extra cost: power reduction, dimming, night switch; LED: CLEVER LIGHT 10 optical system: reflector system for clear, tubular high pressure or for horizontally mounted LLM LED module; FF: directed light (multi layer) provided by an exchangeable, anti-aging lens technology light distribution: asymmetrical wide beam; LLM: extreme wide beam; RWL, FF SW-X: extreme narrow wide beam luminaire head: made of cast and die cast aluminium, powder coated colour: DB 703; other colours on request glazing: ASL 2050 type .01: flat or type .11: slightly curved, clear toughened glass glazing; ASL 2060: flat, clear toughened glass glazing wiring: completely wired; via a clamp within the luminaire head installation: ASL 2050: for top entry  $\varnothing$  76mm and  $\varnothing$  60mm, inclination 2°, 5° 8°, 10°, 13° resp. 15° or for side entry  $\varnothing$  60mm; dispatch standard: for top entry, 2°; ASL 2060: type .01: for side entry  $\varnothing$  60mm, incl. adapter in order to keep the luminaire head parallel to the street even if the bracket is inclined; ASL 2060: type .02: for top entry  $\varnothing$  76mm and  $\varnothing$  60mm, inclination 0°, 5° 10° resp. 15° or for side entry  $\varnothing$  60mm; dispatch standard: 0° accessory: lamp (except for CPO, LED), cable, column, pole accessories, wall, corner or column bracket - to be ordered separately application areas: parkways, cycle lanes, residential and local distribution roads, main streets, boulevards, pedestrian zones, car parks, schools, home for elderly people, hotels, factory premises, squares

## Light output 1



### 1 x High pressure sodium vapour lamp

|                    |          |             |         |
|--------------------|----------|-------------|---------|
| Nominal lamp power | 100 W    | LOR         | 80%     |
| Lamp flux          | 10700 lm | Total flux  | 8580 lm |
| Luminous efficacy  | 78 lm/W  | Total power | 110 W   |
| CCT                | 2000 K   |             |         |
| CRI                | 25       |             |         |



### 1 x Metal halide lamp

|                    |          |             |         |
|--------------------|----------|-------------|---------|
| Nominal lamp power | 100 W    | LOR         | 80%     |
| Lamp flux          | 10600 lm | Total flux  | 8500 lm |
| Luminous efficacy  | 79 lm/W  | Total power | 108 W   |
| CCT                | 3000 K   |             |         |
| CRI                | 90       |             |         |

**Mounting mode**

Pole top mounted

**Shape and measurements**

Length: 34.49 in

Width: 14.61 in

Height: 8.82 in

Weight: 9.6 kg

**Adjustability**

Height adjustable

**Electric**

System power: 108-110 W

**Protection**

IP: 65