

# Product data sheet


AXEL  
9.116.3162.01  
LEIPZIGER LEUCHTEN




IP  
65

Mounting height of 4.00 m provides optimal light distribution. - Housing and frame made of corrosion-resistant and robust cast aluminium, painted - Attachment made of impact-resistant, UV-stabilized polycarbonate with beaded texture, fitted into frame - Lamp and high-quality mirror optics protected by hinged frame witch can be opened with a tool - Reflector parts made of highest grade aluminium, burnished and anodized - All electrical components are arranged on a block, control gear can be switched over - Available in any RAL or DB colour without surcharge - Pole bracket and luminaire mount hot galvanized and painted - Scope of supply includes cylindrically offset pole, dia. 76 mm, reinforced wall, extended earthing strip made of hot galvanized steel, painted Voltage: 230V 50Hz Protected to: IP 65 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



1 x High pressure mercury vapour lamp			
Nominal lamp power	125 W	LOR	54%
Lamp flux	6800 lm	Total flux	3671 lm
Luminous efficacy	27 lm/W	Total power	137 W
CCT	3400 K		
CRI	54		



1 x High pressure mercury vapour lamp			
Nominal lamp power	80 W	LOR	54%
Lamp flux	4000 lm	Total flux	2160 lm
Luminous efficacy	24 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

## Mounting mode

Pole top mounted

## Electric

System power: 89-137 W

## Shape and measurements

Length: 14.96 in

Width: 7.87 in

Height: 7.87 in

## Protection

IP: 65