

# Product data sheet


NORA VIII (W. SHIELD ON SIDE FACING BUILDING CLEAR ATTACHMENT)  
9.778.5521.35  
LEIPZIGER LEUCHTEN



IP  
55

For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of delivery includes special steel post/wall-mounted bracket, painted -Order post dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



### 1 x Compact fluorescent lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 23 W    | LOR         | 85%     |
| Lamp flux          | 1500 lm | Total flux  | 1280 lm |
| Luminous efficacy  | 56 lm/W | Total power | 23 W    |
| CCT                | 2571 K  |             |         |
| CRI                | 90      |             |         |

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 11.81 in

Diameter: 21.26 in

## Electric

System power: 23 W

## Protection

IP: 55