## Product data sheet

MARCEL II (WALL FITTING) 9.842.2052.00

LEIPZIGER LEUCHTEN








For medium and high light requirements, mounting height 3.80 m. - Impact-resistant clear polycarbonate attachment, UV-stabilized, - Reflector lamellae made of premium highest-grade aluminium, burnished and anodized for light guidance and glare limitation - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x High	pressure sodium vapour	lamn
i A i iigii	pressure sociarii vapour	iuiip

TXTIIgit precodire codiaiti vapodi lariip				
Nominal lamp power	100 W	LOR	60%	
Lamp flux	10400 lm	ULOR	10%	
Luminous efficacy	54 lm/W	Total flux	6215 lm	
CCT	2000 K	Total power	115 W	
CBI	25			

Mounting mode

Wall mounted

Shape and measurements

Height: 20.08 in

Diameter: 20.08 in

Electric

System power: 115 W

Protection

IP: 55

Designation labels: CE, F